

Change Type Category (BuildDiff)	Change Type	Description	Example		Change Type Category (BuildMedic)
			Old	New	
General	GENERAL_PROPERTY_DELETE	Covers the deletion of a property to the general properties of the pom.	<properties> <propA>value1</propA> </properties>	<properties> </properties>	Property Change
	GENERAL_PROPERTY_INSERT	Covers the addition of a property to the general properties of the pom.	<properties> </properties>	<properties> <propA>value1</propA> </properties>	Property Change
	GENERAL_PROPERTY_UPDATE	Covers the update of a property's value.	<properties> <propA>value1</propA> </properties>	<properties> <propA>value2</propA> </properties>	Property Change
	LICENSE_DELETE	Extracted if a license is added to the pom.	<licenses> <license> <name>lgpl</name> <url>http://url.at/1gpl-2.1.txt</url> <distribution>repo</distribution> </license> </licenses>	<licenses> </licenses>	Others
	LICENSE_INSERT	Extracted if a license is removed from the pom.	<licenses> </licenses>	<licenses> <license> <name>lgpl</name> <url>http://url.at/1gpl-2.1.txt</url> <distribution>repo</distribution> </license> </licenses>	Others
	LICENSE_UPDATE	Extracted if the content of a license is changed.	<licenses> <license> <name>lgpl</name> <url>http://url.at/1gpl-2.1.txt</url> <distribution>repo</distribution> </license> </licenses>	<licenses> <license> <name>lgpl</name> <url>http://url.at/1gpl-2.2.txt</url> <distribution>repo</distribution> </license> </licenses>	Others
	MODULE_DELETE	Covers the removal of a module.	<modules> <module>diff<-common</module> </modules>	<modules> </modules>	Others
	MODULE_INSERT	Covers the insertion of a module.	<modules> </modules>	<modules> <module>diff<-common</module> </modules>	Others
	MODULE_UPDATE	Covers the update of a module name.	<modules> <module>diff<-common</module> </modules>	<modules> <module>diff<-common-new</module> </modules>	Others
	PARENT_ARTIFACTID_UPDATE	Extracted if the artifactId of a parent pom link is updated.	<parent> <groupId>com.smthg</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </parent>	<parent> <groupId>com.smthg.diff</groupId> <artifactId>parentProj</artifactId> <version>0.0.1</version> </parent>	Dependency ID Change
	PARENT_GROUPID_UPDATE	Extracted if the groupId of a parent pom link is updated.	<parent> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </parent>	<parent> <groupId>com.smthg.differ</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </parent>	Dependency ID Change
	PARENT_UPDATE	Extracted if a child of a parent pom link, except artifactId, groupId, and version, is updated.	<parent> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </parent>	<parent> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> <relativePath>../parent</relativePath> </parent>	Dependency ID Change
	PARENT_VERSION_UPDATE	Extracted if a version of a parent pom link is updated.	<parent> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </parent>	<parent> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.2</version> </parent>	Version Change
	PROFILE_DELETE	When a profile is removed this change is extracted.	<profiles> <profile> <id>jdk8</id> <activation> <jdk>1.8</jdk> </activation> </profile> </profiles>	<profiles> </profiles>	Others
	PROFILE_INSERT	When a profile is added, this change is extracted.	<profiles> </profiles>	<profiles> <profile> <id>jdk8</id> <activation> <jdk>1.8</jdk> </activation> </profile> </profiles>	Others
	PROFILE_UPDATE	Covers all changes to the children of a profile.	<profiles> <profile> <id>jdk8</id> </profile> </profiles>	<profiles> <profile> <id>jdk8</id> <activation> <jdk>1.8</jdk> </activation> </profile> </profiles>	Others
	PROJECT_ARTIFACTID_UPDATE	Extracted if an artifactId of the project is updated.	<project> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </project>	<project> <groupId>com.smthg.diff</groupId> <artifactId>parentProj</artifactId> <version>0.0.1</version> </project>	Dependency ID Change
	PROJECT_GROUPID_UPDATE	Extracted if the groupId of the project is updated.	<project> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </project>	<project> <groupId>com.smthg.differ</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </project>	Dependency ID Change
	PROJECT_NAME_DELETE	Covers the deletion of a name from the project.	<project> <name>BuildDiff</name> </project>	<project> </project>	Others
	PROJECT_NAME_INSERT	Covers the insertion of a name to the project.	<project> </project>	<project> <name>BuildDiff</name> </project>	Others
	PROJECT_NAME_UPDATE	Covers the update of a name to the project.	<project> <name>BuildDiff</name> </project>	<project> <name>BuildDiff</name> </project>	Others
	PROJECT_PACKAGING_DELETE	Covers the deletion of the packaging specification of the project.	<project> <packaging>jar</packaging> </project>	<project> </project>	Others
	PROJECT_PACKAGING_INSERT	Covers the insertion of the packaging specification of the project.	<project> </project>	<project> <packaging>jar</packaging> </project>	Others
	PROJECT_PACKAGING_UPDATE	Extracted when the packaging specification is updated.	<project> <packaging>jar</packaging> </project>	<project> <packaging>war</packaging> </project>	Others
	PROJECT_VERSION_UPDATE	When the version of the project is changed, this change is extracted.	<project> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.1</version> </project>	<project> <groupId>com.smthg.diff</groupId> <artifactId>parent</artifactId> <version>0.0.2</version> </project>	Version Change
	SCM_CONNECTION_DELETE	Covers the removal of the public source code management connection	<scm> <connection>http://con.at</connection> <developerConnection>http://devcon.at</developerConnection> <url>http://url.at</url> </scm>	<scm> <developerConnection>http://devcon.at</developerConnection> <url>http://url.at</url> </scm>	Others
	SCM_CONNECTION_INSERT	Covers the insertion of the public source code management connection	<scm> <developerConnection>http://devcon.at</developerConnection> <url>http://url.at</url> </scm>	<scm> <connection>http://con.at</connection> <developerConnection>http://devcon.at</developerConnection> <url>http://url.at</url> </scm>	Others
	SCM_CONNECTION_UPDATE	Covers the changing of the public source code management connection	<scm> <connection>http://con.at</connection> <developerConnection>http://devcon.at</developerConnection> <url>http://url.at</url> </scm>	<scm> <connection>http://connew.at</connection> <developerConnection>http://devcon.at</developerConnection> <url>http://url.at</url> </scm>	Others





Change Type Category (BuildDiff)	Change Type	Description	Example		Change Type Category (BuildMedic)
			Old	New	
Repository	DIST_SITE_UPDATE	Covers the change of a site in the distribution part.	<distributionManagement> <site> <id>apache.website</id> <url>http://url.com/site</url> </site> </distributionManagement>	<distributionManagement> <site> <id>apache.website</id> <url>http://url.com/sitenew/url</url> </site> </distributionManagement>	Others
	DIST_SNAPSHOT_REPOSITORY_DELETE	Covers the removal of a repository in the distribution part. This covers snapshot repositories.	<distributionManagement> <snapshotRepository> <id>snapshots.jboss.org</id> <name>JBoss Snapshot Repository</name> <url>https://url.com/maven2</url> </snapshotRepository> </distributionManagement>	<distributionManagement> </distributionManagement>	Repository Change
	DIST_SNAPSHOT_REPOSITORY_INSERT	Covers the addition of a repository in the distribution part. This covers snapshot repositories.	<distributionManagement> </distributionManagement>	<distributionManagement> <snapshotRepository> <id>snapshots.jboss.org</id> <name>JBoss Snapshot Repository</name> <url>https://url.com/maven2</url> </snapshotRepository> </distributionManagement>	Repository Change
	DIST_SNAPSHOT_REPOSITORY_UPDATE	Covers the change of a repository in the distribution part. This covers snapshot repositories.	<distributionManagement> <snapshotRepository> <id>snapshots.jboss.org</id> <name>JBoss Snapshot Repository</name> <url>https://url.com/maven2</url> </snapshotRepository> </distributionManagement>	<distributionManagement> <snapshotRepository> <id>snapshots.jboss.org</id> <name>JBoss Snapshot Repository</name> <url>https://url.com/maven3</url> </snapshotRepository> </distributionManagement>	Repository Change
	REPOSITORY_DELETE	This change is extracted if a repository is removed. This concerns repositories outside of the distribution part.	<repositories> <repository> <id>apache.snapshots.https</id> <name>\${distMgmtSnapshotsName}</name> <url>\${distMgmtSnapshotsUrl}</url> </repository> </repositories>	<repositories> </repositories>	Repository Change
	REPOSITORY_INSERT	This change is extracted if a repository is added. This concerns repositories outside of the distribution part.	<repositories> </repositories>	<repositories> <repository> <id>apache.snapshots.https</id> <name>\${distMgmtSnapshotsName}</name> <url>\${distMgmtSnapshotsUrl}</url> </repository> </repositories>	Repository Change
	REPOSITORY_UPDATE	This change is extracted if a repository is updated. This concerns repositories outside of the distribution part.	<repositories> <repository> <id>apache.snapshots.https</id> <name>\${distMgmtSnapshotsName}</name> <url>\${distMgmtSnapshotsUrl}</url> </repository> </repositories>	<repositories> <repository> <id>apache.snapshots.https</id> <name>fixedName</name> <url>\${distMgmtSnapshotsUrl}</url> </repository> </repositories>	Repository Change
	PLUGIN_REPOSITORY_DELETE	This change is extracted if a plugin repository is removed.	<pluginRepositories> <pluginRepository> <id>pluginRepo</id> <name>Plugin Repository</name> <url>http://url.com/maven2</url> </pluginRepository> </pluginRepositories>	<pluginRepositories> <pluginRepository> <id>pluginRepo</id> <name>Plugin Repository</name> <url>http://url.com/maven2</url> </pluginRepository> </pluginRepositories>	Repository Change
Repository	PLUGIN_REPOSITORY_INSERT	This change is extracted if a plugin repository is added.	<pluginRepositories> </pluginRepositories>	<pluginRepositories> <pluginRepository> <id>pluginRepo</id> <name>Plugin Repository</name> <url>http://url.com/maven2</url> </pluginRepository> </pluginRepositories>	Repository Change
	PLUGIN_REPOSITORY_UPDATE	This change is extracted if a plugin repository is updated.	<pluginRepositories> <pluginRepository> <id>pluginRepo</id> <name>Plugin Repository</name> <url>http://url.com/maven2</url> </pluginRepository> </pluginRepositories>	<pluginRepositories> <pluginRepository> <id>pluginRepo</id> <name>Plugin Repository</name> <url>http://url.com/maven3</url> </pluginRepository> </pluginRepositories>	Repository Change
	PLUGIN_VERSION_DELETE	Covers the deletion of a version of a plugin.	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> </plugin> </plugins> </build>	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> </plugin> </plugins> </build>	Version Change
	PLUGIN_VERSION_INSERT	Covers the addition of a version of a plugin.	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> </plugin> </plugins> </build>	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> </plugin> </plugins> </build>	Version Change
Build	PLUGIN_VERSION_UPDATE	Covers the change of a version of a plugin.	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> </plugin> </plugins> </build>	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.2</version> </plugin> </plugins> </build>	Version Change
	PLUGIN_INSERT	Covers the insertion of a plugin.	<build> <plugins> </plugins> </build>	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> </plugin> </plugins> </build>	Others
	PLUGIN_DELETE	Covers the deletion of a plugin.	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> </plugin> </plugins> </build>	<build> <plugins> </plugins> </build>	Others
	PLUGIN_UPDATE	Covers the update of a plugin.	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> </plugin> </plugins> </build>	<build> <plugins> <plugin> <groupId>x.y.test</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> </plugin> </plugins> </build>	Others
	PLUGIN_CONFIGURATION_DELETE	Covers the deletion of a configuration to a plugin.	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> <configuration> <classifier>test</classifier> <something>true</something> <stopNow>false</stopNow> </configuration> </plugin> </plugins> </build>	<build> <plugins> <plugin> <groupId>x.y.z</groupId> <artifactId>a-plugin</artifactId> <version>4.1</version> </plugin> </plugins> </build>	Others

Change Type Category (BuildDiff)	Change Type	Description	Example		Change Type Category (BuildMedic)
			Old	New	
Build	PLUGIN_CONFIGURATION_INSERT	Covers the insertion of a configuration to a plugin.	<pre>&lt;build&gt; &lt;plugins&gt; &lt;plugin&gt; &lt;groupId&gt;x.y.z&lt;/groupId&gt; &lt;artifactId&gt;a-plugin&lt;/artifactId&gt; &lt;version&gt;4.1&lt;/version&gt; &lt;/plugin&gt; &lt;/plugins&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;plugins&gt; &lt;plugin&gt; &lt;groupId&gt;x.y.z&lt;/groupId&gt; &lt;artifactId&gt;a-plugin&lt;/artifactId&gt; &lt;version&gt;4.1&lt;/version&gt; &lt;configuration&gt; &lt;classifier&gt;test&lt;/classifier&gt; &lt;something&gt;true&lt;/something&gt; &lt;stopNow&gt;false&lt;/stopNow&gt; &lt;/configuration&gt; &lt;/plugin&gt; &lt;/plugins&gt; &lt;/build&gt;</pre>	Others
	PLUGIN_CONFIGURATION_UPDATE	Covers a change in the plugin configuration. This covers all inserts, deletions, and updates inside the configuration tag. Will only be extracted once per plugin.	<pre>&lt;build&gt; &lt;plugins&gt; &lt;plugin&gt; &lt;groupId&gt;x.y.z&lt;/groupId&gt; &lt;artifactId&gt;a-plugin&lt;/artifactId&gt; &lt;version&gt;4.1&lt;/version&gt; &lt;configuration&gt; &lt;classifier&gt;test&lt;/classifier&gt; &lt;something&gt;true&lt;/something&gt; &lt;stopNow&gt;false&lt;/stopNow&gt; &lt;/configuration&gt; &lt;/plugin&gt; &lt;/plugins&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;plugins&gt; &lt;plugin&gt; &lt;groupId&gt;x.y.z&lt;/groupId&gt; &lt;artifactId&gt;a-plugin&lt;/artifactId&gt; &lt;version&gt;4.1&lt;/version&gt; &lt;configuration&gt; &lt;classifier&gt;test&lt;/classifier&gt; &lt;something&gt;true&lt;/something&gt; &lt;stopNow&gt;true&lt;/stopNow&gt; &lt;/configuration&gt; &lt;/plugin&gt; &lt;/plugins&gt; &lt;/build&gt;</pre>	Others
	RESOURCE_DELETE	When a resource folder is deleted, this change is extracted.	<pre>&lt;build&gt; &lt;resources&gt; &lt;resource&gt; &lt;directory&gt;./&lt;/directory&gt; &lt;/resource&gt; &lt;/resources&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;resources&gt; &lt;/resources&gt; &lt;/build&gt;</pre>	Others
	RESOURCE_INSERT	When a new resource folder is added, this change is extracted.	<pre>&lt;build&gt; &lt;resources&gt; &lt;/resources&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;resources&gt; &lt;resource&gt; &lt;directory&gt;./&lt;/directory&gt; &lt;/resource&gt; &lt;/resources&gt; &lt;/build&gt;</pre>	Others
	RESOURCE_UPDATE	When a resource folder is changed, this change is extracted.	<pre>&lt;build&gt; &lt;resources&gt; &lt;resource&gt; &lt;directory&gt;./&lt;/directory&gt; &lt;/resource&gt; &lt;/resources&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;resources&gt; &lt;resource&gt; &lt;directory&gt;src/main/otherres&lt;/directory&gt; &lt;/resource&gt; &lt;/resources&gt; &lt;/build&gt;</pre>	Others
	TEST_RESOURCE_DELETE	When a test resource folder is deleted, this change is extracted.	<pre>&lt;build&gt; &lt;testResources&gt; &lt;testResource&gt; &lt;directory&gt;src/test/resources&lt;/directory&gt; &lt;/testResource&gt; &lt;/testResources&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;testResources&gt; &lt;/testResources&gt; &lt;/build&gt;</pre>	Others
	TEST_RESOURCE_INSERT	When a new test resource folder is added, this change is extracted.	<pre>&lt;build&gt; &lt;testResources&gt; &lt;/testResources&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;testResources&gt; &lt;testResource&gt; &lt;directory&gt;src/test/resources&lt;/directory&gt; &lt;/testResource&gt; &lt;/testResources&gt; &lt;/build&gt;</pre>	Others
	TEST_RESOURCE_UPDATE	When a resource test folder is changed, this change is extracted.	<pre>&lt;build&gt; &lt;testResources&gt; &lt;testResource&gt; &lt;directory&gt;./&lt;/directory&gt; &lt;/testResource&gt; &lt;/testResources&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;testResources&gt; &lt;testResource&gt; &lt;directory&gt;src/test/resources&lt;/directory&gt; &lt;/testResource&gt; &lt;/testResources&gt; &lt;/build&gt;</pre>	Others
	PLUGIN_REPORT_SET_UPDATE	Extracted, if a report set is changed.	<pre>&lt;reportSets&gt; &lt;reportSet&gt; &lt;reports&gt; &lt;report&gt;checkstyle&lt;/report&gt; &lt;/reports&gt; &lt;/reportSet&gt; &lt;/reportSets&gt;</pre>	<pre>&lt;reportSets&gt; &lt;reportSet&gt; &lt;reports&gt; &lt;report&gt;findBugs&lt;/report&gt; &lt;/reports&gt; &lt;/reportSet&gt; &lt;/reportSets&gt;</pre>	Others
	SOURCE_DIRECTORY_DELETE	This change is extracted, if a source directory is deleted.	<pre>&lt;build&gt; &lt;sourceDirectory&gt;src/main/myNewJava&lt;/sourceDirectory&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;/build&gt;</pre>	Others
	SOURCE_DIRECTORY_INSERT	This change is extracted, if a source directory is added	<pre>&lt;build&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;sourceDirectory&gt;src/main/myNewJava&lt;/sourceDirectory&gt; &lt;/build&gt;</pre>	Others
	SOURCE_DIRECTORY_UPDATE	This change is extracted, if a source directory is changed.	<pre>&lt;build&gt; &lt;sourceDirectory&gt;src/main/myNewJava&lt;/sourceDirectory&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;sourceDirectory&gt;src/main/allJava&lt;/sourceDirectory&gt; &lt;/build&gt;</pre>	Others
	TEST_SOURCE_DIRECTORY_DELETE	This change is extracted, if a test source directory is deleted.	<pre>&lt;build&gt; &lt;testSourceDirectory&gt;src/test/myJava&lt;/testSourceDirectory&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;/build&gt;</pre>	Others
	TEST_SOURCE_DIRECTORY_INSERT	This change is extracted, if a test source directory is added	<pre>&lt;build&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;testSourceDirectory&gt;src/test/myJava&lt;/testSourceDirectory&gt; &lt;/build&gt;</pre>	Others
	TEST_SOURCE_DIRECTORY_UPDATE	This change is extracted, if a test source directory is changed.	<pre>&lt;build&gt; &lt;testSourceDirectory&gt;src/test/myJava&lt;/testSourceDirectory&gt; &lt;/build&gt;</pre>	<pre>&lt;build&gt; &lt;testSourceDirectory&gt;src/test/allJava&lt;/testSourceDirectory&gt; &lt;/build&gt;</pre>	Others
Team	CONTRIBUTOR_DELETE	Covers the removal of a contributor.	<pre>&lt;contributors&gt; &lt;contributor&gt; &lt;name&gt;Sanne Grinovero&lt;/name&gt; &lt;/contributor&gt; &lt;/contributors&gt;</pre>	<pre>&lt;contributors&gt; &lt;/contributors&gt;</pre>	Others
	CONTRIBUTOR_INSERT	Covers the insertion of a contributor.	<pre>&lt;contributors&gt; &lt;/contributors&gt;</pre>	<pre>&lt;contributors&gt; &lt;contributor&gt; &lt;name&gt;Sanne Grinovero&lt;/name&gt; &lt;/contributor&gt; &lt;/contributors&gt;</pre>	Others
	CONTRIBUTOR_UPDATE	Covers the change of a contributor regarding the child tags.	<pre>&lt;contributors&gt; &lt;contributor&gt; &lt;name&gt;Sanne Grinovero&lt;/name&gt; &lt;/contributor&gt; &lt;/contributors&gt;</pre>	<pre>&lt;contributors&gt; &lt;contributor&gt; &lt;name&gt;Sanne Grinavera&lt;/name&gt; &lt;/contributor&gt; &lt;/contributors&gt;</pre>	Others
	DEVELOPER_DELETE	Covers the removal of a developer.	<pre>&lt;developers&gt; &lt;developer&gt; &lt;id&gt;mmuster&lt;/id&gt; &lt;name&gt;Max Mustermann&lt;/name&gt; &lt;email&gt;max.m@mail.com&lt;/email&gt; &lt;url&gt;http://url.at/muster&lt;/url&gt; &lt;/developer&gt; &lt;/developers&gt;</pre>	<pre>&lt;developers&gt; &lt;/developers&gt;</pre>	Others
	DEVELOPER_INSERT	Covers the insertion of a developer.	<pre>&lt;developers&gt; &lt;/developers&gt;</pre>	<pre>&lt;developers&gt; &lt;developer&gt; &lt;id&gt;mmuster&lt;/id&gt; &lt;name&gt;Max Mustermann&lt;/name&gt; &lt;email&gt;max.m@mail.com&lt;/email&gt; &lt;url&gt;http://url.at/muster&lt;/url&gt; &lt;/developer&gt; &lt;/developers&gt;</pre>	Others
	DEVELOPER_UPDATE	Covers the change of a developer regarding the child tags.	<pre>&lt;developers&gt; &lt;developer&gt; &lt;id&gt;mmuster&lt;/id&gt; &lt;name&gt;Max Mustermann&lt;/name&gt; &lt;email&gt;max.m@mail.com&lt;/email&gt; &lt;url&gt;http://url.at/muster&lt;/url&gt; &lt;/developer&gt; &lt;/developers&gt;</pre>	<pre>&lt;developers&gt; &lt;developer&gt; &lt;id&gt;mmuster&lt;/id&gt; &lt;name&gt;Markus Mustermann&lt;/name&gt; &lt;email&gt;max.m@mail.com&lt;/email&gt; &lt;url&gt;http://url.at/muster&lt;/url&gt; &lt;/developer&gt; &lt;/developers&gt;</pre>	Others